



US009636988B2

(12) **United States Patent**
Pinschmidt

(10) **Patent No.:** **US 9,636,988 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **MOTOR VEHICLE**

(71) Applicant: **AUDI AG**, Ingolstadt (DE)

(72) Inventor: **Udo Pinschmidt**, Gaimersheim (DE)

(73) Assignee: **AUDI AG**, Ingolstadt (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 114 days.

(21) Appl. No.: **14/718,791**

(22) Filed: **May 21, 2015**

(65) **Prior Publication Data**

US 2015/0336453 A1 Nov. 26, 2015

(30) **Foreign Application Priority Data**

May 24, 2014 (DE) 10 2014 007 940

(51) **Int. Cl.**

B60K 6/387 (2007.10)

F16H 48/30 (2012.01)

B60K 6/365 (2007.10)

F16H 48/06 (2006.01)

B60K 17/16 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **B60K 6/365** (2013.01); **B60K 6/387** (2013.01); **B60K 17/165** (2013.01); **F16H 48/06** (2013.01); **F16H 48/30** (2013.01); **B60K 1/00** (2013.01); **B60K 2001/001** (2013.01); **F16H 2048/364** (2013.01); **Y10S 903/902** (2013.01)

(58) **Field of Classification Search**

CPC .. B60K 6/485; B60K 6/387; B60K 2001/001; B60K 1/00; B60K 2006/4808; F16H 48/30; F16H 2048/364; Y10T 477/606

USPC 475/150

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,663,051 B2 * 3/2014 Sten F16H 48/36

475/150

8,874,289 B2 * 10/2014 Tanba B60K 6/387

180/6.2

2007/0123383 A1 5/2007 Yokoyama et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1428256 7/2003

CN 101386267 3/2009

(Continued)

OTHER PUBLICATIONS

European Search Report with respect to counterpart European patent application EP 15 00 1383.

(Continued)

Primary Examiner — Sherry Estremsky

(74) *Attorney, Agent, or Firm* — Henry M. Feiereisen LLC

(57) **ABSTRACT**

A motor vehicle, includes a drive motor for driving the motor vehicle, at least one additional motor and at least one differential for distributing a torque generated by the drive motor and transmitted by a drive shaft to a driven differential element of the differential to two output shafts. The motor vehicle includes a coupling device which can be controlled by a control device, and in a first coupling state directly or indirectly couples the additional motor with an output shaft, thereby rendering the distribution of the drive torque to the output shafts dependent on an additional torque exerted by the additional motor, and in a second coupling state directly or indirectly couples the additional motor with the driven differential element.

17 Claims, 3 Drawing Sheets

